

# FONDO

## Bombato ISO a saldare di testa

Art. 036.0305




Art. 036.0305

**Esecuzione:** ricavato da lamiera in acciaio DD11 decapata fino a  $\varnothing$  323.9 - conforme alle norme EN 10025 ed EN 10111.

**Arichiesta:** certificazione EN 10204 3.1.

### Dimensioni

$\varnothing$	Spessore S mm	H mm	h mm	R mm	r mm	Tolleranze				Peso Kg
						$\varnothing$ mm	Smm	H e h mm	R e r mm	
21.3	2.0	12	4	21	4	$\pm 0.5$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.01
26.9	2.0	14	5	27	4	$\pm 0.5$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.02
33.7	2.3	17	5	34	4	$\pm 0.5$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.03
42.4	2.6	20	5	43	4	$\pm 0.5$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.05
48.3	2.6	21	6	48	4	$\pm 0.5$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.06
60.3	2.9	25	7	60	6	$\pm 1\%$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.12
76.1	2.9	30	9	76	6	$\pm 1\%$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.21
88.9	3.2	33	11	89	8	$\pm 1\%$	+0.5 -15%	$\pm 3.2$	$\pm 10\%$	0.28
101.6	3.6	34	11	102	8	$\pm 1\%$	$\pm 15\%$	$\pm 3.2$	$\pm 10\%$	0.36
108	3.6	35	11	108	8	$\pm 1\%$	$\pm 15\%$	$\pm 3.2$	$\pm 10\%$	0.39
114.3	3.6	36	12	114	8	$\pm 1\%$	$\pm 15\%$	$\pm 3.2$	$\pm 10\%$	0.46
133	4.0	39	12	133	10	$\pm 1\%$	$\pm 15\%$	$\pm 3.2$	$\pm 10\%$	0.59
139.7	4.0	41	12	140	12	$\pm 1\%$	$\pm 15\%$	$\pm 3.2$	$\pm 10\%$	0.62
159	4.5	51	15	159	15	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	1.11
168.3	4.5	56	16	168	15	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	1.23
193.7	5.4	57	17	194	20	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	1.89
219.1	6.3	57	17	220	20	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	2.21
244.5	6.3	60	17	240	25	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	3.16
273	6.3	70	18	270	28	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	3.67
323.9	7.1	87	35	324	32	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	6.30
355.6	8.0	89	40	355	35	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	8.30
368	8.0	95	40	368	37	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	9.20
406.4	8.8	99	45	406	41	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	11.5
419	8.8	105	45	419	42	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	12.8
457.2	10.0	110	50	460	46	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	18.8
508	10.0	120	50	508	51	$\pm 1\%$	$\pm 15\%$	$\pm 5$	$\pm 10\%$	22



Art. 036.0305