


INNESTO A SCARPA

A saldare di testa

Art. 036.0970

Esecuzione: ricavato da tubo in acciaio ST37.0 senza saldatura - conforme alla norma UNI 663-68.


Archiata: certificazione EN10204 2.2.



Art. 036.0970

Dimensioni

Ø	S mm	H mm	h mm	L mm	R mm	Tolleranze			Peso Kg
						D mm	S mm	HhLr mm	
26.9	2.6	38	29	43	32	±0.5	+0.5 -15%	±4	0.05
33.7	3.2	50	40	53	42	±0.5	+0.5 -15%	±4	0.08
42.4	3.2	50	38	67	55	±0.5	+0.5 -15%	±4	0.12
48.3	3.2	64	48	76	60	±0.5	+0.5 -15%	±4	0.25
60.3	3.6	76	58	96	77	±1	+0.5 -15%	±4	0.34
76.1	3.6	88	68	121	100	±1	+0.5 -15%	±4	0.39
88.9	4	88	65	142	122	±1	+0.5 -15%	±4	0.55
101.6	4	91	65	161	138	±1	±15%	±4	0.80
108	4	97	68	172	144	±1	±15%	±4	0.91
114.3	4	102	74	182	160	±1	±15%	±4	1.01
133	4	119	83	213	174	±1	±15%	±4	1.53
139.7	4.5	125	87	222	182	±1	±15%	±4	1.69
159	4.5	143	100	254	212	±1	±15%	±4	2.45
168.3	5.4	151	107	268	224	±1	±15%	±4	2.74
193.7	6.3	174	122	309	258	±1	±15%	±4	4.35
219.1	6.3	197	137	355	295	±1	±15%	±4	6.11
273	7.1	240	155	455	367	±1	±15%	±4	15.65
323.9	8	275	180	537	436	±1	±15%	±4	22.00
355.6	8	-	200	-	-	-	-	-	-
406.4	8.8	-	200	-	-	-	-	-	-
508	11	-	250	-	-	-	-	-	-
610	12.5	-	300	-	-	-	-	-	-



Art. 036.0970