


CURVA

A sella a saldare di testa

Art. 036.0971 3D - 90°

Esecuzione: ricavata da tubo in acciaio ST37.0 senza saldatura - esecuzione e tolleranze secondo DIN 2619.


Arichiesta: certificazione 2.2.



Art. 036.0971

Dimensioni

Ø	S mm	R mm	I mm	Tolleranze				Peso Kg
				Ømm	Smm	Rmm	Imm	
42.2	2.6	48	47.5	±1%	+0.5 -15%	±3%	±10%	0.14
48.3	2.6	57	57	±1%	+0.5 -15%	±3%	±10%	0.19
60.3	2.9	76	76	±1%	+0.5 -15%	±3%	±10%	0.37
76.1	2.9	95	95	±1%	+0.5 -15%	±3%	±10%	0.59
88.9	3.2	114	114.5	±1%	+0.5 -15%	±3%	±10%	0.91
101.6	3.6	133	133.5	±1%	±15%	±3%	±10%	1.38
108	3.6	142	142.5	±1%	±15%	±3%	±10%	1.56
114.3	3.6	152	152.5	±1%	±15%	±3%	±10%	1.77
133	4	181	181	±1%	±15%	±3%	±10%	2.73
139.7	4	190	190.5	±1%	±15%	±4%	±10%	3.03
159	4.5	216	216	±1%	±15%	±4%	±10%	4.35
168.3	4.5	228	228.5	±1%	±15%	±4%	±10%	4.87
193.7	5.4	270	270	±1%	±15%	±4%	±10%	7.5
219.1	6.3	305	305	±1%	±15%	±4%	±10%	11.2
244.5	6.3	340	340	±1%	±15%	±4%	±10%	15
273	6.3	381	381	±1%	±15%	±4%	±10%	19
323.9	7.1	457	457	±1%	±15%	±4%	±10%	30
355.6	8	534	534	±1%	±15%	±4%	±10%	43
368	8	534	534	±1%	±15%	±4%	±10%	44.6
406.4	8.8	610	610	±1%	±15%	±4%	±10%	62



Art. 036.0971