

Bombato ANSI a saldare

Art. 036.1305 Sch.40

Art. 036.2305 Sch.80

Esecuzione: in acciaio ASTM A234 WPB Schedula 40 (**Art. 036.1305**) o Schedula 80 (**Art. 036.2305**) - secondo norme ANSI B 16.9.


Archiata: esecuzione STD, XS, XXS, Sch. 160 - esecuzione in WPL6.



Art. 036.1305

Dimensioni

Ø	Diametro esterno	H mm	Sch.40		Sch.80		Tolleranze		
			S mm	Peso Kg	S mm	Peso Kg	Diametro est.mm	int.mm	H mm
1/2"	21.3	25.4	2.77	0.03	3.73	0.05	-0.8 +1.6	±0.8	±3.2
3/4"	26.7	25.4	2.87	0.06	3.91	0.10	-0.8 +1.6	±0.8	±3.2
1"	33.4	38.1	3.38	0.10	4.55	0.15	-0.8 +1.6	±0.8	±3.2
1 1/4"	42.2	38.1	3.56	0.20	4.85	0.25	-0.8 +1.6	±0.8	±3.2
1 1/2"	48.3	38.1	3.68	0.25	5.08	0.30	-0.8 +1.6	±0.8	±3.2
2"	60.3	38.1	3.91	0.30	5.54	0.35	-0.8 +1.6	±0.8	±3.2
2 1/2"	73	38.1	5.16	0.50	7.01	0.50	-0.8 +1.6	±0.8	±3.2
3"	88.9	50.8	5.49	0.60	7.62	0.90	±1.6	±1.6	±3.2
4"	114.3	63.5	6.02	1.20	8.56	2	±1.6	±1.6	±3.2
5"	141.3	76.2	6.55	2.10	9.52	3	-1.6 +2.4	±1.6	±6.4
6"	168.3	88.9	7.11	3.60	10.97	5	-1.6 +2.4	±1.6	±6.4
8"	219.1	101.6	8.18	5.50	12.70	7	-1.6 +2.4	±1.6	±6.4
10"	273	127	9.27	10	15.06	17	-3.2 +4	±3.2	±6.4
12"	323.9	152	10.31	14	17.45	31	-3.2 +4	±3.2	±6.4
14"	355.6	165	11.12	23	19.05	42	-3.2 +4	±3.2	±6.4
16"	406.4	178	12.70	30	21.41	55	-3.2 +4	±3.2	±6.4
18"	457.2	203	14.27	43	23.80	75	-3.2 +4	±3.2	±6.4
20"	508	229	15.06	60	26.19	100	-3.2 +6.4	±4.8	±6.4
22"	558.8	254	-	85	-	130	-3.2 +6.4	±4.8	±6.4
24"	609.6	267	17.45	98	30.94	155	-3.2 +6.4	±4.8	±6.4



Art. 036.1305